HYDRA VALVE DATA SHEET

ompany Name:ddress:			Date: Person Requesting:		
City:			Phone:		
State:	Zip:		Fax:		
Project Reference:			Email:		
SERVICE CONDITION	S				
Select condition to be controlled:]Flow Rate	Valve Inlet Pressure	Differential Pressure	
	Flow Rate (Q)	Valve Inle Press. (P1	And a second sec	Temperature (T)	Spec. Gravity (SG)
Units (i.e. bbl/d, psi, F°, et	tc.)		- N.		
Max Control Condition	า				
Normal Control Condi	tion				
Min Control Condition					
ADDITIONAL CONDIT	ION COMMENTS				
END CONNECTIONS	Size	Type/Class S			e/Class Sched.
Pipe Thread		F M M	Outlet V/N] M 📄 N/A
Flange			Outlet] [
Bevel For Weld		N/A			N/A
ALVE DESCRIPTION		Select Valve	Style: 🖌		*
Max Pressure					
Max Temp.					
Body Material Stainle	ess Carbon Steel			HCA	Mini
	17-4 PH H1150				
	ungsten Carbide		1		and an
Seal Material PC N	Nitrile FKM				
	ual Automated] Пнсү		csx	Max
	Additional	NOTES		11111	
	EX				
Hydroplex Corporat 230 W. Gloria Switch Lafayette, LA 7050	ion Rd.				
337-233-0626	,,			C.	
ww.hydroplexpumps	s.com			A produc	t of AGI Industries

Patented